

Section 1: Product and Company Identification

Product Name:	Terroxy[®] Resin Systems — Industrial ESD Coating, Part A
Product Use Description:	Resin Compound, Epoxy Resin Systems
Company:	Terrazzo & Marble Supply Companies 77 South Wheeling Road Wheeling, Illinois 60090
Telephone:	847.353.8000
Emergency Telephone:	800.424.9300 - USA 01.703.527.3887 - International

Section 2: Hazards Identification

Classification of the mixture:	Skin irritation – Category 2 Skin sensitization – Category 1 Eye irritation – Category 2 Respiratory tract irritation – Category 3
---------------------------------------	---

Classification according to Regulation (EC) No 1272/2008

GHS Label elements:

Hazard Pictogram:



Signal Word:	Warning
Hazard Statements:	H315 Causes skin irritation H317 May cause an allergic skin reaction H319 Causes serious eye irritation H335 May cause respiratory irritation

Precautionary Statements:	P261 Avoid breathing mist/vapors/spray P264 Wash hands and skin contact areas thoroughly after handling P272 Contaminated work clothing should not be allowed out of the workplace P273 Avoid release to the environment P280 Wear protective gloves/eye/face protection P302, P352 IF ON SKIN: Wash with plenty of soap and water P305, P351, P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do, continue rinsing P333, P313 If skin irritation or rash occurs: Get medical advice/attention P337, P313 If eye irritation persists: Get medical advice/attention P362 Take off contaminated clothing and wash before reuse P391 Collect spillage P501 Dispose of content/container through a waste management company authorized by the local government
----------------------------------	--

Other hazards not classified:	None Known
--------------------------------------	------------

Section 3: Composition / Information on Ingredients

This product is a mixture.

Component	CAS#	Amount
Talc	14807-96-6	3.2-4%
Titanium Dioxide	13463-67-7	1.0-15.0%
Carbon Nanotubes	7440-44-0	0-1.0%
Microcrystalle Amor. Silica	14808-60-7	3.2-4.0%
Lampblack	1333-86-4	0.1-0.2%
Epoxy Resin	25068-99-8	44.8-55.6%
Alkyl C12-C14 Glycidyl Ether	68609-97-2	1.2-2.0%
Glycidyl Ether	2210-79-9	4.7-5.9%
Glass	65997-17-3	5.0-15.0%

Substances listed are present in concentration of 1% or greater, or 0.1% if cited as a potential Carcinogen in the OSHA Hazards communication Standard. Where proprietary ingredient is listed, the identity is available as provided in 29 CFR 1910.1200.

N/E - Not Established
 ALL ingredients are registered on TSCA
 The remaining components are trade secret.

Section 4: First Aid Measures

- General advice:** Seek medical advice. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately.
- Eye contact:** Flush eyes with plenty of water for at least 15 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.
- Skin contact:** Wash with soap and water. Remove contaminated clothing and launder. Get immediate medical attention if irritation develops or persists.
- Ingestion:** Do not induce vomiting. Seek medical attention immediately. Drink two glasses of water of milk to dilute. do not give anything by mouth to an unconscious person. Induced vomiting may lead to aspiration of material into the lungs potentially causing chemical pneumonitis that may be fatal.
- Inhalation:** Move to fresh air. Call a physician if symptoms persist.

Section 5: Fire Fighting Measures

- Flash Point :** 216°F (102°C)
- Autoignition Temperature :** Not Established
- Lower Explosive Limit (% in air) :** Not Established
- Upper Explosive Limit (% in air) :** Not Established
- Extinguishing Media :** Use water spray, foam, dry chemical or carbon dioxide
- Unusual Fire & Explosion Hazards:** Material will burn in a fire.
- Special Fire Fighting Instructions:** Persons exposed to products of combustion should wear self-containing breathing apparatus and full protective equipment.
- Hazardous Combustion Products:** Carbon dioxide, Carbon monoxide

Section 6: Accidental Release Measures

- Special Protection:** Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred.
- Clean-up:** Dike if necessary, contain material with inert absorbent and transfer to containers for disposal. Keep spilled product out of sewers, watersheds, or water systems.
- Transport Emergency Phone Number: (CHEMTREC) 1-800-424-9300**

Section 7: Handling and Storage

- Handling:** Avoid contact with eyes. Avoid contact with skin and eyes. Adhere to work practice rules established by government regulations. Use personal protective equipment. When using, do not eat, drink or smoke.
- Storage:** Store in a cool dry place

Section 8: Exposure Controls / Personal Protection

Personal Protective Equipment:

- Respiratory Protection:** Not required for properly ventilated areas. If vapor or mist is generated and the occupational exposure limit is exceeded, use appropriate NIOSH/MSHA approved self contained breathing equipment or a full face respirator. Respirators should be selected by and used following requirements found in OSHA's respirator standards (29 CFR 1910.134). Not required for properly ventilated areas.
- Ventilation:** Mechanical ventilation required if TLV is expected to be exceeded in confined areas.
- Hand Protection:** Recommend wearing disposable latex or nitrile gloves when mixing to protect against incidental contact. If continuous contact is expected, recommend butyl rubber gloves be worn.
- Eye Protection:** Wear safety glasses with side shields or safety goggles when handling this product. Additionally, wear a face shield when the possibility of splashing liquid exists. Do not wear contact lens. Have an eye wash station available.
- Skin and Body Protection:** Prevent contact with this product. Long sleeve shirts and trouser without cuffs and/or apron is recommended if splashing liquids exists. Other protective equipment may be needed depending on condition use.

Exposure Limit:

Chemical Name	OSHA PEL	ACGIH TLV
Talc	2.0 mg/m ³	2.0 mg/m ³
Hydrous Magnesium Silicate Barium Sulfate	15 mg/m ³	10 mg/m ³
Microcrystalline Amor. Silica	10mg/m ³	0.05 mg/m ³ - Respirable Dust
Lampblack	3.5mg/m ³	3.5mg/m ³
Epoxy Resin	Not Established	Not Established
Alkyl C12-C14 Glycidyl Ether	Not Established	Not Established
Glycidyl Ether	Not Established	Not Established
Glass	Not Established	Not Established

*Unless otherwise noted, all PEL & TLV values are reported as 8 hour time time weighted averages (TWA).

The exposure limits shown here for pigments are for dust exposure. They are not known to be hazardous after blended into a liquid. Wet sanding or sufficient dry-vacuuuming is suggested to eliminate airborne dust, if product is machined or ground. The only other exposure limits established for ingredients of this product apply to nuisance dusts from inert fillers. These fillers are blended into a liquid and pose no hazard as supplied.

Substances listed are present in concentration of 1% or greater, or 0.1% if cited as a potential Carcinogen in the OSHA Hazards Communication Standard. Where proprietary ingredient is listed, the identity is available as provided in 29 CFR 1910.1200.

Section 9: Physical and Chemical Properties

Physical State:	Liquid
Color:	Clear/Custom color varies
Odor:	Sweet Mild
Odor Threshold:	Not established
Weight Per Gallon:	13.19 lbs.
Specific Gravity:	N/A
Solids (% by weight):	100.00
V.O.C.	0.12 lbs/g
pH:	Not Established
Boiling point/Range:	300°F (148°C)
Vapor pressure:	Not Established
Vapor density:	Heavier than air
Evaporator Rate:	Slower than butyl acetate
Octanol/Water Coefficient:	Not Established
Freezing/Melting Point:	Not Established
Flash Point :	216°F (102°C)

Section 10: Reactivity Data

Stability :	Stable under normal conditions.
Chemical Incompatibility:	Not established.
Hazardous Polymerization:	Will not occur.
Hazardous Decomposition Products:	Carbon monoxide, carbon dioxide (CO ₂).

Section 11: Toxicological Information

Chemical Name	Toxicological Dataa
Microcrystalle Amor. Silica	LD50 >22,500 mg/kg Rat
Lampblack	LD50 >8 g/kg Rat - Oral
Epoxy Resin	LD50 11,400 mg/kg Rat LD50 20,000 mg/kg Rabbit
Alkyl C12-C14 Glycidyl Ether	LD50 >19,000 mg/kg Rat LD50 >4,500 mg/kg Rabbit
Glycidyl Ether	LC50 >1,000 ppm 4 hour Rat inhalation LD50 >5,500 mg/kg Rat - Oral LD50 >2,000 mg/kg Rabbit - Dermal LC50 1-10 mg/l Fish

Toxicology Summary : No additional health information available.

Section 12: Ecological Information

Overview: No ecological information available.

Section 13: Disposal Considerations

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Disposal via incineration at an approved facility is recommended. Consult state, local or provincial authorities for more restrictive requirements.

Section 14: Transport Information

Consult Bill of Lading for transportation information

DOT: Not Regulated

IATA: Not Regulated

Section 15: Regulatory Information

OSHA Hazard Communication Standard (29 CFR 1910.1200) Hazard Class(es) Corrosive. Sensitizer.

Country	Regulatory List	Notification
USA	TSCA	Included on Inventory
EU	EINECS	Included on Inventory
Canada	DSL	Included on Inventory
Australia	AICS	Included on Inventory
Japan	ENCS	Included on Inventory
South Korea	ECL	Included on Inventory
China	SEPA	Included on Inventory
Philippines	PICCS	Included on Inventory

This product may contain substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others).

Federal Reporting

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the

Super-fund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

WHMIS STATUS: Unless listed below, This product is not controlled under the Canadian Workplace Hazardous Materials Information System.

D2B D2A

STATE REPORTING

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name	CAS #	Percent
Quartz (Carcinogen)	1408-60-7	0.1-1
Epichlorohydrin (Carcinogen)	TWA 10MG/M3	Not Established
Nickel (metallic)(Carcinogen)	TWA 10MG/M3	Not Established
Epichlorohydrin (Male Reproductive Toxin)		Not Established

Section 16: Other Information

HMIS Rating

Health:	2
Flammability:	1
Reactivity:	0
Physical hazard :	C

This Material Safety Data Sheet, is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standards (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Prepared by Terrazzo & Marble Supply Companies.

Data and recommendations presented herein are based upon ours and other researchers and are believed to be accurate. The products discussed are distributed without warranty (expressed or implied) and the customer shall make his own determination of suitability for his particular purpose.