

PrepMaster® 2817 LP

Ideal for polishing projects under 5000 sq. ft.



Specifications

| | |
|-------------------|--------------------------|
| Motor | Kawasaki 17HP LP |
| Motor RPM | 3,650 rpm |
| Vacuum Hose | 3 in. x 25 ft. |
| Weight | 585 lbs. |
| Tool RPM | 500 rpm @ 3,000 rpm |
| Pressure on Tools | 485 lbs. w/weights |
| Tools Available | All |
| Dimensions | 72" L x 28"W x 53"H |
| Cleaning Path | 12" x 56" sweep |
| Recommened Vaccum | Planet Vac or equivalent |

Productions Rates

| | |
|----------------------|----------------------------|
| Mastic Removal | 350 sq. ft. / hr. per step |
| Thin Set Removal | 400 sq. ft. / hr. per step |
| Mil Coatings Removal | 200 sq. ft. / hr. per step |
| Concrete Polishing | 400 sq. ft. / hr. per step |

Shipping Dimensions & Weights

80" x 36" x 60" 900 lbs.

For more information please contact your local T&M Representative.



464 Northgate Parkway
Wheeling, IL 60090
Local: 847.947.7300
Fax: 847.947.7301
Toll-Free: 877.TM.SLABS

12632 Monarch St. Unit B
Garden Grove, CA 92841
Local: 714.901.1400
Fax: 714.901.1490
Web: www.tmsupply.com