

### Section 1: Product and Company Identification

**Product Name:** Terroxy<sup>®</sup> Resin Systems — Acoustical Membrane, Part B

**Product Use Description:** Curing Agent, Epoxy

**Company:** Terrazzo & Marble Supply Companies  
77 South Wheeling Road  
Wheeling, Illinois 60090

**Telephone:** 847.353.8000  
**Emergency Telephone:** 800.424.9300 - USA  
01.703.527.3887 - International

### Section 2: Hazards Identification

**Classification of the mixture:** Skin corrosion – Category 1B  
Skin sensitization – Category 1  
Serious eye damage – Category 1  
Reproductive toxicity – Category 2  
Acute toxicity – Category 4

**Classification according to Regulation (EC) No 1272/2008**

**GHS Label elements:**

**Hazard Pictogram:**



**Signal Word:** Warning

**Hazard Statements:** H302 Harmful if swallowed  
H314 Causes severe skin burns and eye damage  
H332 Harmful if inhaled  
H335 May cause respiratory irritation

**Precautionary Statements:** P261 Avoid breathing mist/vapors/spray  
P264 Wash hands and skin contact areas thoroughly after handling  
P272 Contaminated work clothing should not be allowed out of the workplace P273 Avoid release to the environment  
P280 Wear protective gloves/eye/face protection  
P301, P330, P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P301, P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell  
P303, P353, P361 IF ON SKIN: Remove/take off immediately all contaminated clothing. Rinse skin with water/shower  
P305, P351, P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do, continue rinsing  
P310: Immediately call a POISON CENTER or doctor/physician  
P333, P313 If skin irritation or rash occurs: Get medical advice/attention  
P362 Take off contaminated clothing and wash before reuse P391 Collect spillage  
P501 Dispose of content/container through a waste management company authorized by the local government

**Other hazards not classified:** None Known

### Section 3: Composition / Information on Ingredients

This product is a mixture.

Component	CAS#	Amount
Nonylphenol	25154-52-3	45.0% - 55.0%
Aliphatic Amines	1761-71-3	5.0% - 20.0%

N/E - Not Established  
 ALL ingredients are registered on TSCA  
 The remaining components are trade secret.

Substances listed are present in concentration of 1% or greater, or 0.1% if cited as a potential Carcinogen in the OSHA Hazards communication Standard. Where proprietary ingredient is listed, the identity is available as provided in 29 CFR 1910.1200.

### Section 4: First Aid Measures

- General advice:** Swallowing this corrosive material may result in severe ulceration, inflammation and possible perforation of the upper alimentary tract, with hemorrhage and fluid loss. Aspiration of this product during induced emesis can result in severe lung injury. If evacuation of stomach is necessary, use method least likely to cause aspiration, such as gastric lavage after endotracheal intubation. Contact a Poison Control Center for additional treatment information.
- Eye contact:** Flush eyes with plenty of water for at least 15 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.
- Skin contact:** Flush at once with potable water for at least 15 minutes. DO NOT attempt to neutralize with chemical agents. Get immediate medical attention. Remove contaminated clothes. Wash before reuse. Destroy contaminated shoes. Get medical attention if swelling and/or irritation occurs.
- Ingestion:** Give water to dilute stomach contents. DO NOT induce vomiting. If vomiting occurs, give fluids again. Get immediate medical attention. Do not give anything by mouth to an unconscious or convulsing person.
- Inhalation:** Move to fresh air. Get medical attention if effects persist.

## Section 5: Fire Fighting Measures

<b>Suitable extinguishing media:</b>	Alcohol-resistant foam Carbon dioxide (CO <sub>2</sub> ) Dry chemical Dry sand Limestone powder
<b>Specific hazards:</b>	May generate ammonia gas. May generate toxic nitrogen oxide gases. Use of water may result in the formation of very toxic aqueous solutions. Do not allow run-off from fire fighting to enter drains or water courses. Incomplete combustion may form carbon monoxide. Downwind personnel must be evacuated. Burning produces obnoxious and toxic fumes.
<b>Special protective equipment for fire-fighters:</b>	Avoid contact with the skin. A face shield should be worn. Use personal protective equipment. Wear positive pressure self contained breathing equipment. Use water to cool containers exposed to fire. Water may be an ineffective extinguishing agent.
<b>Further information :</b>	Vapors are heavier than air and may travel along the ground or be moved by ventilation to ignition sources at locations distant from material handling point. Pressure may build up in containers and create an explosion hazard.

OSHA Flamability Class: Combustible Class III B

## Section 6: Accidental Release Measures

<b>Personal precautions:</b>	Use self-contained breathing apparatus and chemically protective clothing. Wear suitable protective clothing, gloves and eye/face protection. Evacuate personnel to safe areas.
<b>Environmental precautions:</b>	Construct a dike to prevent spreading.
<b>Methods for cleaning up:</b>	Approach suspected leak areas with caution. Contact Terrazzo and Marble Response Center for advice. Place in appropriate chemical waste container.
<b>Additional advice:</b>	If possible, stop flow of product. Avoid contact. Allow only personnel wearing goggles, neoprene or rubber gloves and protective clothing to clean up spill. In confined areas a full face respirator is recommended. Absorb spill with clay, diatomaceous earth or other absorbent materials. Place in disposal containers.

## Section 7: Handling and Storage

<b>Handling:</b>	Avoid contact with eyes. Avoid contact with skin and eyes. Adhere to work practice rules established by government regulations. Use personal protective equipment. When using, do not eat, drink or smoke.
<b>Storage:</b>	Do not store near acids. Keep containers tightly closed in a dry, cool and well-ventilated place. Do not remove labels from empty containers. If mixtures of Part B and Part A are allowed to remain in the mixing container past the pot life deadline, heat and a strong reaction will result.
<b>Technical Measures /Precautions:</b>	Do not store in reactive metal containers.

## Section 8: Exposure Controls / Personal Protection

**Personal Protective Equipment:**

- Respiratory Protection:** Not required for properly ventilated areas. If vapor or mist is generated and the occupational exposure limit is exceeded, use appropriate NIOSH/MSHA approved self contained breathing equipment or a full face respirator. Respirators should be selected by and used following requirements found in OSHA's respirator standards (29 CFR 1910.134).
- Ventilation:** Mechanical ventilation required if TLV is expected to be exceeded in confined areas.
- Hand Protection:** Recommend wearing disposable latex or nitrile gloves when mixing to protect against incidental contact. If continuous contact is expected, recommend butyl rubber gloves be worn.
- Eye Protection:** Wear safety glasses with side shields or safety goggles when handling this product. Additionally, wear a face shield when the possibility of splashing liquid exists. Do not wear contact lens. Have an eye wash station available.
- Skin and Body Protection:** Prevent contact with this product. Long sleeve shirts and trouser without cuffs and/or apron is recommended if splashing liquids exists. Other protective equipment may be needed depending on condition use.

**Exposure Limit:**

Chemical Name	OSHA PEL	ACGIH Exposure limit	AIHA WEEL
nonylphenol	Not Established	Not Established	Not Established
Aliphatic Amines	Not Established	Not Established	Not Established

## Section 9: Physical and Chemical Properties

- Form:** Liquid
- Color:** Light Yellow
- Odor:** Amine-like. Sharp amonia odor.
- Relative density:** 0.98 (H2O = 1)
- Vapor pressure:** < 2.00 mmHg at 70 °F (21 °C)
- VOC:** 0.00
- Density:** 61.179 lb/ft3 (0.98 g/cm3) at 70 °F (21 °C)
- Evaporator Rate:** Not Established
- pH:** 10
- Boiling point/Range:** >430°F (221.1°C)
- Flash point:** >303 °F (150.6°C)
- Water solubility:** Partial

## Section 10: Reactivity Data

<b>Stability :</b>	Stable under normal conditions.
<b>Conditions to Avoid:</b>	Contact with acids such as Hydrochloric or Sulfuric.
<b>Materials to Avoid :</b>	Product slowly corrodes copper, aluminum, zinc and galvanized surfaces. Reaction with peroxides may result in violent decomposition of peroxide possibly creating an explosion. Sodium hypochlorite. Organic acids (i.e. acetic acid, citric acid etc.). Mineral acids. Reactive metals (e.g. sodium, calcium, zinc etc.) Materials reactive with hydroxyl compounds. Oxidizing agents. Epoxy resins under uncontrolled conditions.
<b>Hazardous Decomposition Products:</b>	Nitric Acid Ammonia Nitrogen oxides (NOx). Nitrogen oxide can react with water vapors to form corrosive nitric acid. Carbon monoxide. Carbon dioxide (CO2). Aldehydes Flammable hydrocarbon fragments (e.g., acetylene). When exposed to fire, oxides of Carbon and Nitrogen will be generated.
<b>Hazardous Polymerization:</b>	Will not occur.

## Section 11: Toxicological Information

### Acute Health Hazard

<b>Ingestion:</b>	LD50 : > 1620 mg/kg
<b>Species:</b>	Rat
<b>Method:</b>	Estimated
<b>Inhalation:</b>	LC50(1H) : > 20 mg/l
<b>Species:</b>	Rat
<b>Method:</b>	Estimated
<b>Skin. :</b>	LD50 : > 1,000 mg/kg
<b>Species:</b>	Rabbit.
<b>Method:</b>	Estimated.
<b>Eye irritation/corrosion:</b>	Severe eye irritation.
<b>Acute dermal irritation/corrosion:</b>	Severe skin irritation. Corrosive to the skin of a rabbit.
<b>Sensitization:</b>	Sensation has occurred in laboratory animals after repeated exposure.

### Chronic Health Hazard

The product or a component may be mutagenic, the data is inconclusive.

## Section 12: Ecological Information

### **Ecotoxicity effects**

Aquatic toxicity: No data available.

Toxicity to fish - Components:

Nonylphenol:	LC50 (96 h) : 0.128 mg/l	Species : Fathead Minnow (Pimephales Promelas).
--------------	--------------------------	---

Methylenebiscyclohexanamine, 4,4'-

LC50 (96 h) : 46 - 100 mg/l	Species : Golden Orfe (Leuciscus idus).
-----------------------------	---

Toxicity to daphnia - Components:

Nonylphenol:	EC50 (48 h) : 0.0848 mg/l	Species : Daphnia
--------------	---------------------------	-------------------

Nonylphenol:	EC50 (48 h) : 0.19 mg/l	Species : Daphnia
--------------	-------------------------	-------------------

Methylenebiscyclohexanamine, 4,4'-

EC50 (48 h) : 6.84 mg/l	Species : Daphnia Magna
-------------------------	-------------------------

Toxicity to Algae - Components:

Methylenebiscyclohexanamine, 4,4'-

EC50 (72 h) : 140 - 200 mg/l	Species : Algae
------------------------------	-----------------

Toxicity to other organisms:

No data available.

### **Persistence and degradability**

Mobility: No data available.

Bioaccumulation: No data available.

Bioaccumulation - Components:

Nonylphenol: Moderate bioaccumulation potential.

## Section 13: Disposal Considerations

### **Waste from residues / unused products:**

Dispose in an approved incinerator or an approved landfill. Contact supplier if guidance is required.

### **Contaminated packaging:**

Dispose of container and unused contents in accordance with federal, state, and local requirements.

## Section 14: Transport Information

**CFR**

**Proper shipping name:** Amines, liquid, corrosive, n.o.s. (4,4'-Methylenebiscyclohexanamine, Nonylphenol)  
**Class:** 8  
**UN/ID No.:** UN2735  
**Packing group:** III  
**NAERG No.:** 153

**IATA**

**Proper shipping name:** Amines, liquid, corrosive, n.o.s. (4,4'-Methylenebiscyclohexanamine, Nonylphenol)  
**Class:** 8  
**UN/ID No.:** UN2735  
**Packing group:** III

**IMDG**

**Proper shipping name:** Amines, liquid, corrosive, n.o.s. (4,4'-Methylenebiscyclohexanamine, Nonylphenol)  
**Class:** 8  
**UN/ID No.:** UN2735  
**Packing group:** III

**CTC**

**Proper shipping name:** Amines, liquid, corrosive, n.o.s. (4,4'-Methylenebiscyclohexanamine, Nonylphenol)  
**Class:** 8  
**UN/ID No.:** UN2735  
**Packing group:** III

## Section 15: Regulatory Information

OSHA Hazard Communication Standard (29 CFR 1910.1200) Hazard Class(es) Corrosive. Sensitizer.

Country	Regulatory List	Notification
USA	TSCA	Included on Inventory
EU	EINECS	Included on EINECS inventory or polymer substance, monomers included on EINECS inventory are no longer polymer.
Canada	DSL	Included on Inventory
Australia	AICS	Included on Inventory
Japan	ENCS	Included on Inventory
South Korea	ECL	Included on Inventory
China	SEPA	Included on Inventory
Philippines	PICCS	Included on Inventory

EPA SARA Title III Section 312 (40 CFR 370) Hazard Classification:

Acute Health Hazard

EPA SARA Title III Section 313 (40 CFR 372) Component(s) above 'de minimus' level:

None.

US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65):

This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other harm.

WHMIS Hazard Classification:

Toxic Material Causing Other Toxic Effects, Corrosive Material

## Section 16: Other Information

### HMIS Rating

**Health:** 3  
**Flammability:** 1  
**Reactivity:** 0  
**Physical hazard:** C

Prepared by Terrazzo & Marble Supply Companies.

**Data and recommendations presented herein are based upon ours and other researchers and are believed to be accurate. The products discussed are distributed without warranty (expressed or implied) and the customer shall make his own determination of suitability for his particular purpose.**