

# Safety Data Sheet (SDS)

Revision Date: 9/2023

Product Name:	Terroxy® Resin Systems — Industrial ESD Coating, Part B
Product Use Description:	Curing Agent, Epoxy
Company:	Terrazzo & Marble Supply Companies 77 South Wheeling Road Wheeling, Illinois 60090
Telephone: Emergency Telephone:	847.353.8000 800.424.9300 - USA 01.703.527.3887 - International

### Section 2: Hazards Identification

	Skin corrosion – Category 1B Skin sensitization – Category 1 Serious eye damage – Category 1 Reproductive toxicity– Category 2 Acute toxicity – Category 4
Classification apporting to Page	, 0 ,

Classification according to Regulation (EC) No 1272/2008

**GHS Label elements:** 

Hazard Pictogram:



Signal Word: Hazard Statements:	Warning H302 Harmful if swallowed H314 Causes severe skin burns and eye damage H332 Harmful if inhaled H335 May cause respiratory irritation
Precautionary Statements:	<ul> <li>P261 Avoid breathing mist/vapors/spray</li> <li>P264 Wash hands and skin contact areas thoroughly after handling</li> <li>P272 Contaminated work clothing should not be allowed out of the workplace P273 Avoid release to the environment</li> <li>P280 Wear protective gloves/eye/face protection</li> <li>P301, P330, P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.</li> <li>P301. P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you fell unwell</li> <li>P303, P353, P361 IF ON SKIN: Remove/take off immediately all contaminated clothing. Rinse skin with water/shower</li> <li>P305, P351, P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do, continue rinsing</li> <li>P310: Immediately call a POISON CENTER or doctor/physician</li> <li>P333, P313 If skin irritation or rash occurs: Get medical advice/attention</li> <li>P362 Take off contaminated clothing and wash before reuse P391 Collect spillage</li> <li>P501 Dispose of content/container through a waste management company authorized by the local government</li> </ul>
Other hazards not classified:	None Known



### Section 3: Composition / Information on Ingredients

This product is a mixture.

Component	CAS#	Amount	
Polyetheramine	9046-10-0	19.1-23.6%	Substances listed are present
Nonylphenol	25154-52-3	16.0-19.8%	concentration of 1% or greater, or 0.1
Phenylmethylalc2Hydroxytoluene	100-51-6	16.0-19.8%	if cited as a potential Carcinogen in th
Polyamine	NJTSR	16.0-19.9%	OSHA Hazards communication Standar
1,3 Cyclohexanedimethanamine	2579-20-6	16.0-19.8%	Where proprietary ingredient is listed, th
			identity is available as provided in 29 C

N/E - Not Established

ALL ingredients are registered on TSCA

The remaining components are trade secret.

#### Section 4: First Aid Measures

1910.1200.

General advice:	Swallowing this corrosive material may result in severe ulceration, inflammation and possible perforation of the upper alimentary tract, with hemorrhage and fluid loss. Aspiration of this product during induced emesis can result in severe lung injury. If evacuation of stomach is necessary, use method least likely to cause aspiration, such as gastric lavage after endotracheal intubation. Contact a Poison Control Center for additional treatment information.
Eye contact:	Flush eyes with plenty of water for at least 15 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.
Skin contact:	Flush at once with potable water for at least 15 minutes. DO NOT attempt to neutralize with chemical agents. Get immediate medical attention. Remove contaminated clothes. Wash before reuse. Destroy contaminated shoes. Get medical attention if swelling and/or irritation occurs.
Ingestion:	Give water to dilute stomach contents. DO NOT induce vomiting. If vomiting occurs, give fluids again. Get immediate medical attention. Do not give anything by mouth to an unconscious or convulsing person.
Inhalation:	Move to fresh air. Get medical attention if effects persist.



Section 5: Fire Fighting Measures		
Suitable extinguishing media:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Dry sand Limestone powder	
Specific hazards:	May generate ammonia gas. May generate toxic nitrogen oxide gases. Use of water may result in the formation of very toxic aqueous solutions. Do not allow run-off from fire fighting to enter drains or water courses. Incomplete combustion may form carbon monoxide. Downwind personnel must be evacuated. Burning produces obnoxious and toxic fumes.	
Special protective equipment for fire-fighters:	Avoid contact with the skin. A face shield should be worn. Use personal protective equipment. Wear positive pressure self contained breathing equipment. Use water to cool containers exposed to fire. Water may be an ineffective extinguishing agent.	
Further information : OSHA Flamability Class: Combu	Vapors are heavier than air and may travel along the ground or be moved by ventilation to ignition sources at locations distant from material handling point. Pressure may build up in containers and create an explosion hazard. Justible Class III B	

	Section 6: Accidental Release Measures
Personal precautions:	Use self-contained breathing apparatus and chemically protective clothing. Wear suitable protective clothing, gloves and eye/face protection. Evacuate personnel to safe areas.
Environmental precautions:	Construct a dike to prevent spreading.
Methods for cleaning up:	Approach suspected leak areas with caution. Contact Terrazzo and Marble Response Center for advice. Place in appropriate chemical waste container.
Additional advice:	If possible, stop flow of product. Avoid contact. Allow only personnel wearing goggles, neoprene or rubber gloves and protective clothing to clean up spill. In confined areas a full face respirator is recommended. Absorb spill with clay, diatomaceous earth or other absorbent materials. Place in disposal containers.

	Section 7: Handling and Storage
Handling:	Avoid contact with eyes. Avoid contact with skin and eyes. Adhere to work practice rules established by government regulations. Use personal protective equipment. When using, do not eat, drink or smoke.
Storage:	Do not store near acids. Keep containers tightly closed in a dry, cool and well-ventilated place. Do not remove labels from empty containers. If mixtures of Part B and Part A are allowed to remain in the mixing container past the pot life deadline, heat and a strong reaction will result.
Technical Measures /Precautions:	Do not store in reactive metal containers.

## Section 8: Exposure Controls / Personal Protection

#### Personal Protective Equipment:

Respiratory Protection:	Not required for properly ventilated exposure limit is exceeded, use app equipment or a full face respirato requirements found in OSHA's respi	ropriate NIOSH/ <i>N</i> r. Respirators sho	ASHA approved self cor ould be selected by ar	ntained breathing
Ventilation:	Mechanical ventilation required if I	LV is expected to	be exceeded in confi	ined areas.
Hand Protection:	Recommend wearing disposable incidental contact. If continuous c worn.			
Eye Protection:	Wear safety glasses with side shields wear a face shield when the possi Have an eye wash station available	bility of splashing		
Skin and Body Protection:	Prevent contact with this product. is recommended if splashing liquid depending on condition use.			
Exposure Limit:	Chemical Name	OSHA PEL	ACGIH Exposure limit	AIHA WEEL
	Polyetheramine	Not Established	Not Established	Not Established
	Nonylphenol	Not Established	Not Established	Not Established
	Phenylmethylalc2Hydroxytoluene	Not Established	Not Established	Not Established
	Polyamine	Not Established	Not Established	Not Established
	1,3 Cyclohexanedimethanamine	Not Established	Not Established	Not Established

# Section 9: Physical and Chemical Properties



	Section 10: Reactivity Data
Stability : Conditions to Avoid: Materials to Avoid :	Stable under normal conditions. Not Applicable. Product slowly corrodes copper, aluminum, zinc and galvanized surfaces. Reaction with peroxides may result in violent decomposition of peroxide possibly creating an explosion. Sodium hypochlorite. Organic acids (i.e. acetic acid, citric acid etc.). Mineral acids. Reactive metals (e.g. sodium, calcium, zinc etc.) Nitrous acid and other nitrosating agents. Materials reactive with hydroxyl compounds. Oxidizing agents. Epoxy resins under uncontrolled conditions.
Hazardous Decomposition Products:	Nitric acid. Ammonia Nitrogen oxides (NOx). Nitrogen oxide can react with water vapors to form corrosive nitric acid. Carbon monoxide. Carbon dioxide (CO2). Aldehydes Flammable hydrocarbon fragments (e.g., acetylene). When exposed to fire, oxides of Carbon and Nitrogen will be generated.
Hazardous Polymerization:	Will not occur.

# Section 11: Toxicological Information

Acute Health Hazard	
Ingestion:	LD50 : > 500 mg/kg
Species:	Rat
Method:	Estimated
Inhalation:	LC50(1H) : > 20 mg/l
Species:	Rat
Method:	Estimated
Skin. :	LD50 : > 2,000 mg/kg
Species:	Rabbit.
Method:	Estimated.
Eye irritation/corrosion:	Severe eye irritation.
Acute dermal	
irritation/corrosion:	Severe skin irritation. Corrosive to the skin of a rabbit.
Sensitization:	Sensation has occurred in laboratory animals after repeated exposure.
<u>Chronic Health Hazard</u>	
	The product or a component may be mutagenic, the data is inconclusive.



# Section 12: Ecological Information

No ecological information available. **Overview:** 

	Section 13: Disposal Considerations			
Waste from residues / unused products:	Contact supplier if guidance is required.			
Contaminated packaging:	Dispose of container and unused contents in accordance with federal, state, and local requirements.			
Section 14: Transport Information				
<u>CFR</u> Proper shipping name: Class: UN/ID No.: Packing group: NAERG No.:	Amines, liquid, corrosive, n.o.s. (Polyetheramine, Nonylphenol) 8 UN2735 III 153			
<u>IATA</u> Proper shipping name: Class: UN/ID No.: Packing group:	Amines, liquid, corrosive, n.o.s. (Polyetheramine, Nonylphenol) 8 UN2735 III			
<u>IMDG</u> Proper shipping name: Class: UN/ID No.: Packing group:	AMINES, LIQUID, CORROSIVE, N.O.S. (Polyetheramine, Nonylphenol) 8 UN2735 III			
<u>CTC</u> Proper shipping name: Class: UN/ID No.: Packing group:	AMINES, LIQUID, CORROSIVE, N.O.S. (Polyetheramine, Nonylphenol) 8 UN2735 III			



#### Section 15: Regulatory Information

OSHA Hazard Communication Standard (29 CFR 1910.1200) Hazard Class(es)Corrosive. Sensitizer.

Country	Regulatory List	Notification
USA	TSCA	Included on Inventory
EU	EINECS	Included on EINECS inventory or polymer substance, monomers included on EINECS inventory are no longer polymer.
Canada	DSL	Included on Inventory
Australia	AICS	Included on Inventory
Japan	ENCS	Included on Inventory
South Korea	ECL	Included on Inventory
China	SEPA	Included on Inventory
Philippines	PICCS	Included on Inventory

#### EPA SARA Title III Section 312 (40 CFR 370) Hazard Classification:

Acute Health Hazard

EPA SARA Title III Section 313 (40 CFR 372) Component(s) above 'de minimus' level:

None.

US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65):

This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other harm.

WHMIS Hazard Classification:

Toxic Material Causing Other Toxic Effects, Corrosive Material

### Section 16: Other Information

#### **HMIS Rating**

Health:	3
Flammability:	1
Reactivity:	0
Physical hazard:	С

Prepared by Terrazzo & Marble Supply Companies.

Data and recommendations presented herein are based upon ours and other researchers and are believed to be accurate. The products discussed are distributed without warranty (expressed or implied) and the customer shall make his own determination of suitability for his particular purpose.